Screws





Wood and metal studs

Sizes: 1-5/8", 2-1/4"

Features:

- · Sharp point drives easily.
- Bugle head drives flush with no counter sink.
- Phillips drive is less visible than square drive.

Available in all storeWALL panel colors. Rust resistant zinc plate.

The #6 screw is designed for wood studs and metal studs from 20 to 25 gauge. Pre-drilling is not required.

Concrete

Sizes: 1", 1-3/4"

Features:

- 4Cut serrated Spax screw point threads concrete.
- MULTIhead design countersinks screw head.
- Drive with Phillips, square or Unidrive.

Available in all storeWALL panel colors. Rust resistant zinc plate.

Use 1" for poured concrete. Use 1-3/4" for concrete block.

Predrill concrete with a 1/8" carbide bit.

This #8 screw can also be used with wood studs and metal studs to 25 gauge without pre-drilling.

TIP: Wood studs in old construction can be exceptionally hard. Pre-drilling the screw hole can avoid screw breakage.

TIP: You can paint your own favorite fastener. See Installation Tips - Painting screws.

Quantity Use

Estimate 80 screws per carton of 8 foot storeWALL, or, 2 screws per square foot of installation. This quantity assumes you are driving screws in every other slot with studs 16" on center.

